

GB 1460864
JAN 1977

GROUP. 3.21
CLASS. 285
RECORDED

ICATION

1460864

1 460 864

- (21) Application No. 11308/74 (22) Filed 14 March 1974
(23) Complete Specification filed 13 June 1975
(44) Complete Specification published 6 Jan. 1977
(51) INT CL⁷ F16L 19/00
(52) Index at acceptance F2G 25A 2B
(72) Inventors JACK BEACHAM and BRIAN BERNARD DEELEY

GREAT BRITAIN, (19)
GROUP. 3.21
CLASS. 285
RECORDED



(54) IMPROVEMENTS IN PIPE UNIONS

- (71) PANY LII
Delta Road
hereby dec
pray that a
the method
be particu
following s
This inve
providing
first and se
which the
more partic
comprising
flange and
member hi
adjacent to
being adap
with the fir
of the tub
member by
co-operation
between the
flanges of the
nut and the
tubular mem
ber on tighte
ning of the
union nut on
to the first
member, and
a further me
tallic member
secured to the
other end of
the tubular
member and
adapted to
screw-thread
edly engage
with the se
cond screw-
threaded me
mber, the u
nion nut bei
ng held capt
ive on the
tubular me
mber and sa
id further
member wh
ich has a
sufficiently
large trans
verse dimen
sion to pre
vent passag
e of the u
nion nut ov
er said fu
rther mem
ber.
- Unions of this kind have been used for connecting gas appliances together, for connecting a meter service governor to a meter for example.
- It is known to connect the tubular member to said further member after assembly of the union nut onto the tubular member by screwing and brazing the tubular member to said further member.
- This is, however, an expensive operation, requires testing of the seal between the two members, and has a high reject rate. Moreover the seal between the two members may be broken when the union is
- SPEY Q67 *A1007Y/01 *GB 1460-864
Mfg. pipe union for incompatible threaded members - by threading tubular member, fitting union nut, screwing end member on and deforming threaded joint
SPERRYN & CO LTD 14.03.74-GB-011308
(06.01.77) F16L-19
A pipe union for two incompatible threaded members is formed from a stamped union nut (1) held captive on a stamped and machined tubular member (2) secured to a forged member (3). The nut is tapped and the member (3) has an external tapered thread (6). The union is formed, by first forming a thread on one end of the tubular member (2) and then passing the nut over this end. The member (3) is then screwed onto the tubular member and a ball plunger or roller burnishing tool inserted to expand the joint to bind the threads of the joint together to form a gas tight seal. 13.6.75 (4pp)
-
- joint to bind the threads of the joint together to form a gas tight seal. 13.6.75 (4pp)
- other end is formed with an external screw thread for engagement with a co-operating internal screw thread formed in said further member.
- Usually the further member will be formed with an external radially extending polygonal flange for engagement by a spanner when the further member is tightened in use to the second member. It is this polygonal flange which would prevent assembly of the union nut onto the tubular member if the tubular member were to be made integral with the further member.
- The tubular member and the further member may be made of any suitable metal but preferably they are made of brass.
- The expansion of the joint between the tubular member and the further member is conveniently performed by cold forming with a ball plunger or roller burnishing tool.
- The invention will now be further described, by way of example only, with reference to the accompanying drawing which is an axial cross section of a completed brass union adapted to secure an externally screw-threaded first member to an internally screw-threaded second member to provide fluid communication therebetween.

tion of the
method of
and set forth
end of the
er member
threads,
the tubular
other end,
er to said
permanently
nt between
aid further
radially.
the further
a drop of a
applied to
per at said
other end is
formed with
an external
screw thread
for engage
ment with
a co-operat
ing internal
screw thread
formed in
said further
member.
Usually the
further mem
ber will be
formed with
an external
radially ex
tending po
lygonal fla
nge for en
gagement
by a span
ner when
the further
member is
tightened
in use to
the second
member.
It is this
polygonal
flange wh
ich would
prevent as
sembly of
the union
nut onto
the tubul
ar membe
r if the tu
bular mem
ber were
to be ma
de integ
ral with
the furth
er membe
r.
The tubul
ar membe
r and the
further m
ember ma
y be made
of any su
itable me
tal but p
referably
they are
made of
brass.
The expan
sion of the
joint bet
ween the
tubular
membe
r and the
further
membe
r is con
veniently
perform
ed by col
d forming
with a b
all plun
ger or r
oller bur
nishing
tool.
The inve
ntion wil
l now be
further
described,
by way
of exam
ple only,
with re
ference
to the a
ccompan
ying dra
wing wh
ich is an
axial cr
oss sect
ion of a
comple
ted brass
union a
dapted
to secu
re an ex
ternally
screw-
threaded
first me
mber to
an inte
rnally
screw-
threaded
second
membe
r to pro
vide flu
id comm
unicati
on there
between.

BEST AVAILABLE COPY

The union comprises a stamped union nut 1 held captive on a stamped and machined tubular member 2 secured to a further member 3 which is a forging.

5 The union nut 1 is internally screw-threaded for engagement with external screw threads on a first member, not shown, and is provided with an internal radial flange 4 for engagement with an external radial flange 5 which is an integral part of one end of the tubular member 2. When the union nut 1 is screwed in use onto the first member the tubular member 2 is drawn towards the first member by the engagement between the flanges 4 and 5.

15 The further member 3 is formed with an external tapered screw thread 6 for engagement with an internal co-operating screw thread of a second member, not shown, and is provided with an integral polygonal radial flange 7 for engagement by a spanner during tightening in use of the further member 7 to the second member.

25 Initially the other end 8 of the tubular member 3 comprises a plain sleeve. Prior to assembly of the union nut 1 onto the sleeve the exterior of said other end 8 is formed with a plain external screw thread for engagement with a complementary screw thread formed internally of the further member 3. The union nut is then assembled onto the tubular member 2 by passing it over said other end 8 of the tubular member. The tubular member and the further member are then screwed together and a ball plunger or roller burnishing tool is inserted into the joint between the members by passing it through the further member 3, and the joint between the members is expanded radially over the distance A by cold forming to increase the internal diameter D of the joint and to bind the screw threads of the joint together to form a gas-tight seal between the tubular member 2 and the further member 3.

45 In one example the initial diameter D is 0.875 inches and a plunging tool of 0.925" diameter is used. The diameter D is thus increased by slightly more than 4% of its initial value.

50 In order to increase the break-loose torque of the joint between the members 2 and 3 a drop of a screw-thread locking material such as that sold under the Registered Trade Mark 'LOCTITE' STÜDLOCK (OR GRADE 75) is applied to the middle part of one of the screw threads before the members 2 and 3 are screwed together.

WHAT WE CLAIM IS:—

1. A method of manufacturing a pipe union of the kind set forth comprising forming said other end of the tubular member and said further member with complementary screw threads, assembling the union nut onto the tubular member by passing it over said other end of the tubular members, screwing said tubular member to said further member, and then permanently deforming the screw-threaded joint between said tubular member and said further member by expanding the joint radially.

2. The method according to claim 1 in which the tubular member is formed with its screw thread prior to assembling the union nut onto the tubular member.

3. The method according to claim 1 or claim 2 in which prior to screwing the tubular member to said further member screw-thread locking material is applied to at least one of the co-operating screw threads.

4. The method according to any of the preceding claims in which the co-operating screw threads comprise an external screw thread formed on the tubular member and an internal screw thread formed on said further member.

5. The method according to any of the preceding claims in which the expansion of the joint is performed by cold forming.

6. The method according to claim 5 in which the joint between the tubular member is expanded by insertion of a ball plunger.

7. The method according to claim 5 in which the joint between the tubular member is expanded by a roller burnishing tool.

8. The method according to any of the preceding claims in which the tubular member and said further member are of brass.

9. The method according to any of the preceding claims in which the internal diameter of the joint between the tubular member and said further member is increased by more than four per cent of the initial diameter.

10. The method according to claim 1 and substantially as described with reference to the accompanying drawing.

11. A pipe union of the kind set forth produced by the method according to any of the preceding claims.

12. A pipe union of the kind set forth manufactured according to the method of claim 10 and substantially as described with reference to the accompanying drawing.

The union comprises a stamped union nut 1 held captive on a stamped and machined tubular member 2 secured to a further member 3 which is a forging.

5 The union nut 1 is internally screw-threaded for engagement with external screw threads on a first member, not shown, and is provided with an internal radial flange 4 for engagement with an external radial flange 5 which is an integral part of one end of the tubular member 2. When the union nut 1 is screwed in use onto the first member the tubular member 2 is drawn towards the first member by the engagement between the flanges 4 and 5.

15 The further member 3 is formed with an external tapered screw thread 6 for engagement with an internal co-operating screw thread of a second member, not shown, and is provided with an integral polygonal radial flange 7 for engagement by a spanner during tightening in use of the further member 7 to the second member.

20 Initially the other end 8 of the tubular member 3 comprises a plain sleeve. Prior to assembly of the union nut 1 onto the sleeve the exterior of said other end 8 is formed with a plain external screw thread for engagement with a complementary screw thread formed internally of the further member 3. The union nut is then assembled onto the tubular member 2 by passing it over said other end 8 of the tubular member. The tubular member and the further member are then screwed together and a ball plunger or roller burnishing tool is inserted into the joint between the members by passing it through the further member 3, and the joint between the members is expanded radially over the distance A by cold forming to increase the internal diameter D of the joint and to bind the screw threads of the joint together to form a gas-tight seal between the tubular member 2 and the further member 3.

45 In one example the initial diameter D is 0.875 inches and a plunging tool of 0.925 inch diameter is used. The diameter D is thus increased by slightly more than 4% of its initial value.

50 In order to increase the break-loose torque of the joint between the members 2 and 3 a drop of a screw-thread locking material such as that sold under the Registered Trade Mark 'LOCTITE' STULOCK (OR GRADE 75) is applied to the middle part of one of the screw threads before the members 2 and 3 are screwed together.

WHAT WE CLAIM IS:—

60 1. A method of manufacturing a pipe union of the kind set forth comprising forming said other end of the tubular member and said further member with complementary screw threads, assembling the union nut onto the tubular member by passing it over said other end of the tubular members, screwing said tubular member to said further member, and then permanently deforming the screw-threaded joint between said tubular member and said further member by expanding the joint radially.

70 2. The method according to claim 1 in which the tubular member is formed with its screw thread prior to assembling the union nut onto the tubular member.

75 3. The method according to claim 1 or claim 2 in which prior to screwing the tubular member to said further member screw-thread locking material is applied to at least one of the co-operating screw threads.

80 4. The method according to any of the preceding claims in which the co-operating screw threads comprise an external screw thread formed on the tubular member and an internal screw thread formed on said further member.

85 5. The method according to any of the preceding claims in which the expansion of the joint is performed by cold forming.

90 6. The method according to claim 5 in which the joint between the tubular member is expanded by insertion of a ball plunger.

95 7. The method according to claim 5 in which the joint between the tubular member is expanded by a roller burnishing tool.

100 8. The method according to any of the preceding claims in which the tubular member and said further member are of brass.

105 9. The method according to any of the preceding claims in which the internal diameter of the joint between the tubular member and said further member is increased by more than four per cent of the initial diameter.

110 10. The method according to claim 1 and substantially as described with reference to the accompanying drawing.

11. A pipe union of the kind set forth produced by the method according to any of the preceding claims.

115 12. A pipe union of the kind set forth manufactured according to the method of claim 10 and substantially as described with reference to the accompanying drawing.

BARKER, BRETTELL & DUNCAN
Chartered Patent Agents
Agents for the Applicants
138 Hagley Road
Edgbaston
Birmingham B16 9PW.

Printed for Her Majesty's Stationery Office by the Courier Press, Leamington Spa, 1977.
Published by the Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from
which copies may be obtained.

BEST AVAILABLE COPY